

LED luminaries Manufacturer and Exporter

Driverless led spot light Specification

Product: Driverless COB led spot light

Model No.: GNH-AC-GU10-H-6W; GNH-AC-GU10-D-6W

Date: <u>Dec 24th, 2014</u>



GNH-AC-GU10-H-6W



GNH-AC-GU10-D-6W



LED luminaries Manufacturer and Exporter

I. Product introduction

Characteristics


- 1. No driver thus it can avoid the failure of driver
- 2. Dimmable matching different dimmer control. like PMW, Silicon controlled rectifier etc almost 85%dimmer
- 3. 50W halogen replacement
- 4. Scientific thermal design, longer life span
- AC LED technology makes LEDs work directly by AC110-130V/AC220-240V without any driver, we call it driver-free light. These LEDs can be connected directly to normal power supplies (usually 110V at 60HZ or 230V at 50HZ).
- 6. Original Samsung AC COB, low life decaying rate
- 7. Clean and pure light effect, energy saving
- 8. Warranty: 4 Years
- 9. Driverless, 50,000hrs life span
- 10. Easy to pass CE SAA Certificates for its driverless
- 11. 100% pass CE RoHS certificates for its no ICs Capacitors Inductance and Transformers



LED luminaries Manufacturer and Exporter

II. Specifications, parameters

1. Dimensional Drawing(Unit: mm):



2. Contrastive Picture for traditional and driverless led spot light







LED luminaries Manufacturer and Exporter

3. LED spot light technical parameters (*** Note: Different CCT LEDS has different optical properties. The deviation is less than 5%***)

Model No.	Po wer	Voltage (AC)	Dimension	Lighting Source	ССТ	Materi al	Flux(LM)	Beam angle	CRI(Ra
GNH-AC-GU 10-H-6W	6W	110-120 220-240	Φ50*H54mm; Φ50*H56.5mm ;Φ50*H60mm; Φ50*H63mm	Samsun g AC COB	2700-600 0K	6063 Alumi num	380LM ±5%; 420LM ±5%; 480LM ±5%; 510LM ±5%	24°/38°/ 60°	75-80
GNH-AC-GU 10-D-6W	6W	110-120 220-240	Φ50*H52mm; Φ50*H55mm; Φ50*H57.5mm ;Φ50*H60mm	Samsun g AC COB	2700-600 0K	6063 Alumi num	400LM ±5%; 420LM ±5%; 480LM ±5%	38°/60°	75-80

4. Brightness Contrast:








LED luminaries Manufacturer and Exporter


5. LEDs Lumen Attenuation:

Testing condition: None break operation



6. Packing details

Part No.	Packing Box	Outer	Gross Weight	Net weight	
		Carton			
GNH-AC-GU10-H-6W		280*584*190mm	10.8KGS	7.8KG	
GNH-AC-GU10-D-6W	51*51*75mm	280°384°190IIIII	10.6KGS	7.0NG	





LED luminaries Manufacturer and Exporter

7. Application:

As usual they are widely used Hotels, Hospitals, Commercial Complexes, Conference / Meeting rooms, Factories & Offices, Residential / Institution Buildings, Schools and so on.

