

LED luminaries Manufacturer and Exporter

Soft pink LED T8 tube specification

Item: GNH-T8

Dimension(mm): L600*Φ26; L900*Φ26; L1200*Φ26; L1500*Φ26

Power: 9W; 12W; 18W; 22W

Date: Dec 30th, 2014



Tel: +86 755 81471320 **Fax:** +86 755 81711339 www.greenoughled.com Email: sales@greenoughled.com



LED luminaries Manufacturer and Exporter

I. Product introduction

Materials

Our pink T8 LED tubes use transparent or milky PC cover and aluminum material, high quality SMD2835 LED light source.

Characteristics

- 1. **Energy saving**. LED tube light can save you more than 50% in energy cost compare to conventional tube.
- Long life and environmental protection. LED tube light uses LEDs with long lifetime more than 40,000 hours. It has no ultraviolet radiation. It offers full environmental protection. It has no hazardous materials like mercury or lead entering the environment.
- 3. The pink meat LED tube is designed to replace Osram Natural color 76 meat tubes
- 4. **Direct replacement of conventional tube.** Except for electronic ballasts, our LED tubes can directly replace conventional florescent tube, no need to remove any ballast.
- 5. Good heat dissipation. LED tubes use unique heat sinking device with good heat dissipation.
- 6. **Low heat**. The total power consumption is less than half of the traditional tube. The surface temperature will be less than 50 degrees while it is in normal use.
- 7. **Constant current driver.** New internal high efficiency constant current driver with thermal and short circuit protection system can work under unstable voltage (voltage range is AC85V-265V) with minimum maintenance and insures that every LED operates steadily and within parameters.
- 8. **Healthy to eyes.** Instant start, no flickering, no humming. Aluminum isolation avoids EMC electronic wave disturbance.
- 9. Good and bright lighting is important for production, working and live. It can not only give the people comfortable feeling, but also help to find the smudgy.


www.greenoughled.com **Tel**: +86 755 81471320 **Fax**: +86 755 81711339 **Email**: sales@greenoughled.com



LED luminaries Manufacturer and Exporter

II. Specifications, parameters

1. Dimensional Drawing:



All dimension units are millimeter.

All dimension tolerance is ±1mm unless otherwise noted.


2. Pink LED tube light technical parameters (*** Note: Different CCT LEDS has different optical properties. The deviation is less than 5%***)

Model No.	LED No. (pcs	Voltage (AC)	Size (MM)	Pow er	Housing Material	LED style	Flux(LM	Bea m angl e	CRI(Ra)
GNH-T8-60-48-9W	48	100-240V	L600*Φ26	9W	Aluminum	2835 SMD	550LM	120°	≥70
GNH-T8-90-72-12W	72	100-240V	L900*Ф26	12W	Aluminum	2835 SMD	950LM	120°	≥70
GNH-T8-120-96-18W	96	100-240V	L1200*Ф26	18W	Aluminum	2835 SMD	1500LM	120°	≥70
GNH-T8-150-120-22W	120	100-240V	L1500*Ф26	22W	Aluminum	2835 SMD	1550LM	120°	≥70




LED luminaries Manufacturer and Exporter

3. Photometric drawing (just for reference)



Illuminance Maintenance





Tel: +86 755 81471320 **Fax:** +86 755 81711339 www.greenoughled.com Email: sales@greenoughled.com



LED luminaries Manufacturer and Exporter


4. External Structure:





5. Installation


1. Inductive Fixture (Magnetic Ballast)



Way 1: Replace with LED starter Starter AC100V-254V


Turn off the power, remove fluorescent tube remove fluorescent starter and replace with LED starter. Place LED tube into position.

2. Electronic Fixture (Electronic Ballast)




B: Traditional fluorescent tube with electronic fixture. (Electronic Ballast)

A: Traditional fluorescent tube with inductive fixture. (Magnetic Ballast)



Turn off the power, remove fluorescent tube and fluorescent starter. Bypass magnetic ballast(Qualified Electrician ONLY). Replace with LED tube.



Turn off the power, remove fluorescent tube. Qualified Electrician needs to bypass or remove the electronic ballast, reconnect for single ended power input, and then replace with LED tube.

www.greenoughled.com **Tel**: +86 755 81471320 **Fax**: +86 755 81711339 **Email**: sales@greenoughled.com



LED luminaries Manufacturer and Exporter

6. Packing details

Part No.	Package dimension	Gross Weight		
T8-60	650X215X223mm , 25pcs/carton	7.90kg		
T8-90	950X215X223mm , 25pcs/carton	10.60kg		
T8-120	1260X215X223mm , 25pcs/carton	12.90kg		
T8-150	156X215X223mm , 25pcs/carton	14.80kg		



 $\textbf{www.greenoughled.com} \qquad \textbf{Tel:} \ +86\ 755\ 81471320 \qquad \textbf{Fax:} \ +86\ 755\ 81711339 \qquad \textbf{Email:} \ \text{sales@greenoughled.com}$



LED luminaries Manufacturer and Exporter

7. Applications

Special LED Tube with pink color for supermarket, eat, sausage, fruit makes them look more fresh and appetizing.

Typically it can be used to replace the special OSRAM Natural SPLIT Control, color 76" T8 fluorescent tube.

- Shop with meat, baked food
- Supermarket with fruit and vegetable
- Laboratories, special plastic and metal industry
- Other Special food industries.



Tel: +86 755 81471320 Fax: +86 755 81711339 www.greenoughled.com Email: sales@greenoughled.com